

INDUSTRIAL COMPONENT DATA

MINI MCR-EX-SD-16-50-LP 1157869 PHOENIX CONTACT Ex i-Valve control block to activate solenoid valves with in..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI MCR-EX-SD-16-50-LP



Manufacturer	PHOENIX CONTACT
MPN / Reference	MINI MCR-EX-SD-16-50-LP
Catalog number	1157869
Category	Isolation amplifier
Minimum order	1 Pcs
Document ID	EO-69AB38C76F
Generated	2026-08-05

Product Overview

Ex i-Valve control block to activate solenoid valves with intrinsic safety in the Ex zone. no-load voltage: 16 V DC, current limitation: 50 mA, Standard configuration, Loop-powered, Safety Integrity Level (SIL, IEC 61508): 3, Screw connection

Ex i, Valve control block for operating intrinsically safe solenoid valves in the Ex. zone No-load voltage: 16 V, current limiting: 50 mA, Loop-powered, Safety Integrity Level (SIL, IEC61508): 3, Screw connection

Ex i-Valve control module for the control of Ex i solenoid valves in the Ex zone. no-load voltage: 16 V DC, current limitation: 50 mA, Standard configuration, Loop Powered, Safety Integrity Level (SIL, IEC 61508): 3, Screw connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Technical dataArticle featuresProduct Type Valve control module

Product Family MINI Analog Pro

Electrical characteristicsGalvanic isolation

Overvoltage Category II (<= 5000 m)

Degree of pollution 2 (<= 5000 m)

Galvanic Isolation Input/Output IEC/EN 61010-1

Standards/Provisions IEC/EN 61010-1

Rated insulation voltage 300 V_{Eff}

Test voltage 2.5 kV AC (50 Hz, 60 s)

isolation Dual/reinforced insulation

Galvanic Isolation Input/Output IEC/EN 60079-11
Standards/Provisions IEC/EN 60079-11
Rated insulation voltage 265 V_{Eff}
Galvanic Isolation Input/Output IEC/EN 60079-7
Standards/Provisions IEC/EN 60079-7
Rated insulation voltage 251 V_{Eff}
Feeding
Supply voltage range Self-powered in a loop, no external power supply required
Input < 1.4 W
Input DataSignal: Voltage
Number of inputs 1
Input signal, voltage 19.2 V DC ... 30 V DC (24 V DC, -20 % ... +25 %)
Output DataSignal: Voltage
Number of outputs 1
Output voltage ≥ 10.7 V DC (50 mA)
Output Resistor $\geq 103 \Omega$ (internal resistance R_{the})
Current limiting > 50 mA
Response time < 50 ms
No-load voltage > 16 V DC
Resistant to short circuits Yes
Connection dataConductor cross-section AWG (converted according to IEC)
Link Screw connection
Stripping length 10 mm
Thread M3
Rigid conductor cross-section 0.2 mm² ... 1.5 mm² (with lug)
0.14 mm² ... 2.5 mm² (without lug)
Flexible conductor cross-section 0.14 mm² ... 2.5 mm²
Conductor cross-section AWG 24 ... 12 (flexible)
Tightening torque 0.5 Nm ... 0.6 Nm
EX DataEx Installation (EPL) Gc
Div. 2
Ex i Cir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI MCR-EX-SD-16-50-LP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.