

INDUSTRIAL COMPONENT DATA

REL-MR-110DC/21-21AU 2961228 PHOENIX CONTACT Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-MR-110DC/21-21AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-MR-110DC/21-21AU
Catalog number	2961228
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-7BBAFB1891
Generated	2026-08-01

Product Overview

Single relay

Plug-in miniature power relay, with multilayer gold contact, 2 switched contacts, input voltage 110 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2961228

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 304 (C-5-2017)

GTIN 4017918157982

Weight per Piece (excluding packing) 14.970 g

Custom tariff number 85364900

Country of origin AT (Austria)

Dimensions

Width 12.7 mm

Height 29 mm

Depth 15.7 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 110 V DC
Typical input current at UN 4.1 mA
Typical response time 7 ms
Typical release time 3 ms
Coil resistance 26600 $\pm$ 15 % (at 20 °C)
Power dissipation for nominal condition 0.45 W
Contact side
Contact type 2 PDT
Type of switch contact Single contact
Contact material AgNi, hard gold-plated
Maximum switching voltage 30 V AC
36 V DC
Minimum switching voltage 100 mV (at 10 mA)
Min. switching current 1 mA (at 24 V)
Maximum inrush current 50 mA
Limiting continuous current 50 mA
Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)
Contact side (with destroyed gold layer)
Contact material AgNi
Note the following values are applicable if a gold layer is destroyed
Maximum switching voltage 250 V
Minimum switching voltage 5 V (at 10 mA)
Limiting continuous current 8 A
Maximum inrush current 50 A (20 ms)
Min. switching current 10 mA (At 5 V)
Interrupting rating (ohmic load) max. 190 W (at 24 V DC)
85 W (at 48 V DC)
60 W (at 60 V DC)
44 W (at 110 V DC)
60 W (at 220 V DC)
2000 VA (for 250 V AC)
Switching capacity 2 A (at 24 V, DC13)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-MR-110DC/21-21AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.