

INDUSTRIAL COMPONENT DATA

REL-MR- 24AC/21-21AU 2961464 PHOENIX CONTACT Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-MR-24AC/21-21AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-MR-24AC/21-21AU
Catalog number	2961464
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-F18A3CCA79
Generated	2026-08-04

Product Overview

Single relay

Plug-in miniature power relay, with multi-layer gold contact, 2 switched contacts, input voltage 24 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data

Orderkey 2961464

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 304 (C-5-2017)

GTIN 4017918937874

Weight per Piece (excluding packing) 16.110 g

Custom tariff number 85364190

Country of origin AT (Austria)

Dimensions

Width 12.7 mm

Height 29 mm

Depth 15.7 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Coil side

Nominal input voltage UN 24 V AC

Mains frequency 50/60 Hz

Typical input current at UN 32 mA (at 50 Hz)

24 mA (At 60 Hz)

Typical response time 3 ms ... 12 ms (depending on phase relation)

Typical release time range 2 ms ... 9 ms (depending on phase relation)

Coil resistance 350 $\pm$ 10 % (at 20 °C)

Power dissipation for nominal condition 0.77 W

Contact side

Contact type 2 PDT

Type of switch contact Single contact

Contact material AgNi, hard gold-plated

Maximum switching voltage 30 V AC

36 V DC

Minimum switching voltage 100 mV (at 10 mA)

Min. switching current 1 mA (at 24 V)

Maximum inrush current 50 mA

Limiting continuous current 50 mA

Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)

Contact side (with destroyed gold layer)

Contact material AgNi

Note the following values are applicable if a gold layer is destroyed

Maximum switching voltage 250 V AC/DC

Minimum switching voltage 5 V (at 10 mA)

Limiting continuous current 8 A

Maximum inrush current 50 A (20 ms)

Min. switching current 10 mA (At 5 V)

Interrupting rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-MR-24AC/21-21AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.