

INDUSTRIAL COMPONENT DATA

MK4DS 1,5/ 2-5,08 BK 1701607 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MK4DS 1,5/ 2-5,08 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MK4DS 1,5/ 2-5,08 BK
Catalog number	1701607
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-C49738CBE1
Generated	2026-08-05

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 15 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of potentials: 8, number of rows: 4, number of poles per row: 2, article family: MK4DS 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1701607

Packing unit 1

GTIN 4046356548748

Custom tariff number 85369010

Item properties

Brief article description PCB terminal block

Range of articles MK4DS 1,5

Pitch 5.08 mm

Number of positions 2

Connection method Screw connection with tension sleeve

Drive form screw head Slotted (L)

Screw thread M3

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 4

Number of connections 8

Number of potentials 8

Electrical parameters

Rated current 15 A

Rated insulation voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Connection capacity

Conductor cross section solid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

Conductor cross section AWG / kcmil 26 ... 14

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 1.5 mm²

2 conductors with same cross section, solid 0.14 mm² ... 1 mm²

2 conductors with same cross section, flexible 0.14 mm² ... 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 0.5 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 0.5 mm²

Stripping length 7 mm

Torque 0.5 Nm ... 0.6 Nm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics hot-dip tin-plated

Metal surface te...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MK4DS 1,5/ 2-5,08 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.