

INDUSTRIAL COMPONENT DATA

MKDS 1/ 2-3,81 HT BK R24 1003562 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 200 V, p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 1/ 2-3,81 HT BK R24



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 1/ 2-3,81 HT BK R24
Catalog number	1003562
Category	Printed circuit board terminal
Minimum order	280 Pcs
Document ID	EO-D6130943EF
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, rated voltage: 200 V, pitch: 3,81 mm, number of poles: 2, type of connection: Connection by screw with capsule-traction, assembly: Soldering THR, color: black

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 200 V, nominal section: 1.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, family of articles: MKDS 1/.. -HT, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping shape: L Longitudinal slot, mounting: Weld THR, conductor/printed circuit board connection direction: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, Packing Type: 24mm Wide Strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Terminal for printed circuit board, rated current: 13,5 A, rated voltage: 200 V, pitch: 3,81 mm, number of poles: 2, type of connection: Connection by screw with capsule-traction, assembly: Soldering THR, direction for connection conductor/pcb: 0 °, color: black

Data commercial

Key order One million three thousand five hundred sixty two

Packing unit 280 pcs

Key selling AAABCA -

Minimum order quantity 280 pcs

EAN Four trillion fifty five billion six hundred twenty six million four hundred seventy one thousand one hundred ninety eight

Unit weight (excluding packaging) 2,600 g

Tariff number tariff Eighty five million three hundred sixty nine thousand ten

Dimensions

Length [l] 7,3 mm

Step 3,81 mm

Average 3,81 mm

Width [w] 7,61 mm

Height of construction 8.5 mm

Height [h] 12 mm

Length of pin [P] 3.5 mm

Separation between rods 3.5 mm

Diameter hole 1.1 mm

Overview

Family of articles MKDS 1/..-HT

Nominal cross section 1 mm²

Surface pin welding

Number of poles Two

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Space of time for the intended use (FEUP): 50 years

You will find information about hazardous substances in the manufacturer's declaration in the "Downloads" tab

Ratings

eCl@ss

eCl@ss 5.1 Twenty seven million two hundred sixty one thousand one hundred

eCl@ss 6.0 Twenty seven million two hundred sixty one thousand one hundred

eCl@ss 7.0 Twenty seven million four hundred forty thousand four hundred one

eCl@ss 8.0 Twenty seven million four hundred forty....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 1/ 2-3,81 HT BK R24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.