

INDUSTRIAL COMPONENT DATA

MKDS 1/ 6-3,81 HT BK P1,65 1005620 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 200 V,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 1/ 6-3,81 HT BK P1,65



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 1/ 6-3,81 HT BK P1,65
Catalog number	1005620
Category	Printed circuit board terminal
Minimum order	120 Pcs
Document ID	EO-D714597D4F
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, rated voltage: 200 V, pitch: 3,81 mm, number of poles: 6, type of connection: Connection by screw with capsule-traction, assembly: Soldering THR, color: black

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 200 V, nominal section: 1.5 mm², number of potentials: 6, number of rows: 1, number of poles per row: 6, family of articles: MKDS 1/.. -HT, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, mounting: Weld THR, conductor/printed circuit board connection direction: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 1.65 mm, number of solder pins per potential: 1, Packing Type: Boxed Packed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 1/ 6-3,81 HT BK P1,65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.