

INDUSTRIAL COMPONENT DATA

MKDS 10 HV/ 3-ZB-10,16 SZS SO 1714466 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 100..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 10 HV/ 3-ZB-10,16 SZS SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 10 HV/ 3-ZB-10,16 SZS SO
Catalog number	1714466
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-9E4E271556
Generated	2026-08-06

Product Overview

Terminal for printed circuit board, rated voltage: 1000 V, pitch: 10,16 mm, number of poles: 3, color: green
Terminal block for printed circuit board, nominal current: 76 A, nominal voltage (III/2): 1000 V, nominal cross-section: 16 mm², number of potentials: 3, number of rows: 1, number of poles per row: 3, article family: MKDS 10 HV, pitch: 10.16 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Zigzag Pins W, Pin length [P]: 5 mm, number of soldering pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 10 HV/ 3-ZB-10,16 SZS SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.