

INDUSTRIAL COMPONENT DATA

MKDS 1,5/ 2-5,08 BD:24V-GND 1715224 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 400 V..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 1,5/ 2-5,08 BD:24V-GND



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 1,5/ 2-5,08 BD:24V-GND
Catalog number	1715224
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-A2FEA8AE94
Generated	2026-08-06

Product Overview

Terminal for printed circuit board, rated voltage: 400 V, pitch: 5,08 mm, number of poles: 2, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: green

Terminal block for printed circuit board, nominal current: 17.5 A, dimensioning voltage (III/2): 400 V, nominal section: 1.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: MKDS 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, Conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]:3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 1,5/ 2-5,08 BD:24V-GND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.