

INDUSTRIAL COMPONENT DATA

MKDS 1,5/ 2-5,08 BK BDWH:5-6 1026548 PHOENIX CONTACT Terminal for printed circuit board, rated voltage: 400 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 1,5/ 2-5,08 BK BDWH:5-6



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 1,5/ 2-5,08 BK BDWH:5-6
Catalog number	1026548
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-6BA1AB1C7F
Generated	2026-08-06

Product Overview

Terminal for printed circuit board, rated voltage: 400 V, pitch: 5,08 mm, number of poles: 2, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: black

Printed circuit board terminal, rated current: 17.5 A, sizing voltage (III/2): 400 V, nominal section: 1.5 mm², Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, item family: MKDS 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Wave welding, Connection direction conductor/printed circuit board: 0°, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]:3.5 mm, packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 1,5/ 2-5,08 BK BDWH:5-6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.