

INDUSTRIAL COMPONENT DATA

SPT 16/ 2-V-10,0-ZB GYBD-BT+SO 1705095 PHOENIX CONTACT Terminal block for printed circuit board, rated curre..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 16/ 2-V-10,0-ZB GYBD-BT+SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 16/ 2-V-10,0-ZB GYBD-BT+SO
Catalog number	1705095
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-A920452AC4
Generated	2026-08-06

Product Overview

Terminal block for printed circuit board, rated current: 76 A, rated voltage: 1000 V, pitch: 10 mm, number of poles: 2, connection type: Push-in spring connection, mounting: Wave soldering, color: gray

Terminal block for printed circuit board, nominal current: 76 A, nominal voltage (III/2): 1000 V, nominal section: 16 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, family of articles: SPT 16/.. -V, pitch: 10 mm, connection type: Push-in spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 90 °, color: gray, Pin arrangement: Zigzag pins W, Pin length [P]: 4.1 mm, number of solder pins per potential: 3, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

PCB terminal block, nominal current: 76 A, nom. voltage: 1000 V, pitch: 10 mm, number of positions: 2, connection method: Push-in spring connection, mounting: Wave soldering, color: gray

Your advantages

Time saving push-in connection, tools not requiredDefined contact force ensures that contact remains stable over the long termClamping space opened by means of fixed screwdriver enables convenient conductor connectionUnrestricted 600-V-UL approval thanks to compact zig-zag pinningVertical connection enables multi-row arrangement on the PCBKey Commercial Data

Orderkey 1705095

Packing unit 1

GTIN 4046356753432

Custom tariff number 85369010

Electrical parameters

Rated current 76 A

Rated insulation voltage (III/2) 1000 V

Rated surge voltage (III/2) 8 kV

Connection capacity

Conductor cross section solid 0.75 mm² ... 16 mm²

Conductor cross section flexible 0.75 mm² ... 16 mm²

Conductor cross section AWG / kcmil 20 ... 4

Conductor cross section flexible, with ferrule without plastic sleeve 0.75 mm² ... 16 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.75 mm² ... 4 mm²

Stripping length 18 mm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics hot-dip tin-plated

Material data - housing

Housing color gray (7042)

Insulating material PA

CTI according to IEC 60112 600

Flammability rating according to UL 94 V0

Glow wire flammability index...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 16/ 2-V-10,0-ZB GYBD-BT+SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.