

INDUSTRIAL COMPONENT DATA

MKDS 3/ 3-5,08 BD:DN,L,UP SO 1709638 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 400 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 3/ 3-5,08 BD:DN,L,UP SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 3/ 3-5,08 BD:DN,L,UP SO
Catalog number	1709638
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-AECD8E93
Generated	2026-08-04

Product Overview

Terminal for printed circuit board, rated voltage: 400 V, pitch: 5,08 mm, number of poles: 3, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: green

Terminal block for printed circuit board, nominal current: 24 A, dimensioning voltage (III/2): 400 V, nominal section: 2.5 mm², Number of potentials: 3, Number of rows: 1, Number of poles per row: 3, family of articles: MKDS 3, pitch: 5.08 mm, type of connection: Screw connection with traction capsule, mounting: Wave soldering, Connection Direction Driver/PCB: 0°, Color: Green, Packaging Type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 3/ 3-5,08 BD:DN,L,UP SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.