

INDUSTRIAL COMPONENT DATA

MKDS 3/ 5 BK GP 1535628 PHOENIX CONTACT PCB terminal, rated current: 24 A, rated voltage (III/2): 400 V, rat..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 3/ 5 BK GP



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 3/ 5 BK GP
Catalog number	1535628
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-316437A673
Generated	2026-08-04

Product Overview

PCB terminal, rated current: 24 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of rows: 1, number of poles per row: 5, item family: MKDS 3, pitch: 5 mm, connection type: Screw connection with pull capsule, screw clamping form: L Longitudinal groove, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Black, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 5mm, Number of Solder Pins by Potential: 1, Packing Type: Boxed Packaging. The item can be aligned with different pole numbers!

PCB terminal block, nominal current: 24 A, rated voltage (III/2): 400 V, nominal cross section: 2.5 mm², number of rows: 1, number of positions per row: 5, product range: MKDS 3, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: black, Pin layout: Linear pinning, Solder pin [P]: 5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard. The article can be aligned to create different nos. of positions!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Terminals M

Product type Printed circuit board terminal

Product family MKDS 3

Number of positions 5

Pitch 5 mm

Number of rows 1

Pin layout Linear pinning
Solder pins per potential 1
Electrical properties Nominal current I_N 24 A
Nominal voltage U_N 400 V
Degree of pollution 3
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 400 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection data Connection technology
Type PC terminal block can be aligned
Nominal cross section 2.5 mm²
Conductor connection
Connection method Screw connection with tension sleeve
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with same cross section, solid 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.75 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1.5 mm²
Stripping length 8 mm
Tightening torque 0.5 Nm ... 0.6 Nm
Conductor connection
Connection method Screw connection with tension sleeve
Strippin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 3/ 5 BK GP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.