

INDUSTRIAL COMPONENT DATA

MKDS 5/ 2-9,5 GY BD:PE,U 1781722 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 5/ 2-9,5 GY BD:PE,U



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 5/ 2-9,5 GY BD:PE,U
Catalog number	1781722
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-DFA8EF2F99
Generated	2026-08-04

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 32 A, nominal voltage (III/2): 1000 V, nominal cross-section: 4 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: MKDS 5, pitch: 9.52 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0°, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, number of soldering pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1781722

Packing unit 1

GTIN 4046356590921

Custom tariff number 85369010

Dimensions

Length [l] 12.05 mm

Pitch 9.52 mm

Dimension a 9.52 mm

Width [w] 19.04 mm

Height 21.5 mm

Height [h] 26.5 mm

Solder pin [P] 5 mm

Hole diameter 1.3 mm

General

Range of articles MKDS 5

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 690 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 32 A

Nominal cross section 4 mm²

Solder pin surface

Internal cylindrical gage A4

Stripping length 8 mm

Number of positions 2

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1.5 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 1.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.75 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 2.5 mm²

Standards and Regulations

Connection in acc. with stan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 5/ 2-9,5 GY BD:PE,U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.