

INDUSTRIAL COMPONENT DATA

MKDS 5/ 3-9,5 BD:T1-T3 1752248 PHOENIX CONTACT Printed circuit board terminal, rated current: 32 A, rated vo..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 5/ 3-9,5 BD:T1-T3

	Manufacturer	PHOENIX CONTACT
	MPN / Reference	MKDS 5/ 3-9,5 BD:T1-T3
	Catalog number	1752248
	Category	Printed circuit board terminal
	Minimum order	1000 Pcs
	Document ID	EO-916F43A572
	Generated	2026-08-06

Product Overview

Printed circuit board terminal, rated current: 32 A, rated voltage (III/2): 1000 V, rated cross-section: 4 mm², number of rows: 1, number of poles per row: 3, item family: MKDS 5, pitch: 9.52 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Green, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 5mm, Number of Solder Pins per Potential: 1, Packaging Type: Boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 5/ 3-9,5 BD:T1-T3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.