

INDUSTRIAL COMPONENT DATA

MKDS 5 HV/10-9,52-Z H1L TS 1714608 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 1000 V..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 5 HV/10-9,52-Z H1L TS



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 5 HV/10-9,52-Z H1L TS
Catalog number	1714608
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-8FABEEEEAA
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, rated voltage: 1000 V, pitch: 9,52 mm, number of poles: 10, type of connection:

Connection by screw with capsule-traction, assembly: wave Soldering, color: green

Terminal block for printed circuit board, nominal current: 32 A, dimensioning voltage (III/2): 1000 V, nominal section: 4 mm², Number of potentials: 10, Number of rows: 1, Number of poles per row: 10, family of articles: MKDSV 5 HV, pitch: 9.52 mm, type of connection: Screw connection with traction capsule, mounting: Wave soldering, Driver/PCB connection direction: 0°, Color: Green, Pin arrangement: Linear pin arrangement, Pin length [P]: 5.2mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 5 HV/10-9,52-Z H1L TS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.