

INDUSTRIAL COMPONENT DATA

MKDS 5 HV/ 5-9,52 BK 1820353 PHOENIX CONTACT Printed circuit board terminal, rated current: 32 A, rated volt..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 5 HV/ 5-9,52 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 5 HV/ 5-9,52 BK
Catalog number	1820353
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-A4C28963FA
Generated	2026-08-04

Product Overview

Printed circuit board terminal, rated current: 32 A, rated voltage (III/2): 1000 V, rated cross-section: 4 mm², number of rows: 1, number of poles per row: 5, article family: MKDS 5 HV, pitch: 9.52 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Black, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 5mm, Number of Solder Pins per Potential: 1, Packaging Type: Boxed Packaged

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 5 HV/ 5-9,52 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.