

INDUSTRIAL COMPONENT DATA

MKDS 5N HV/ 6-ZB-6,35 SZS 1003330 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 1000 V,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 5N HV/ 6-ZB-6,35 SZS



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 5N HV/ 6-ZB-6,35 SZS
Catalog number	1003330
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-BCA384DB28
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, rated voltage: 1000 V, pitch: 6.35 mm, number of poles: 6, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: green

Terminal block for printed circuit board, nominal current: 41 A, nominal voltage (III/2): 1000 V, nominal section: 4 mm², number of potentials: 6, number of rows: 1, number of poles per row: 6, family of articles: MKDS 5 N HV, pitch: 6.35 mm, type of connection: Screw connection with traction capsule, mounting: Wave soldering, Connection direction conductor/printed circuit board: 0 °, color: green, Pin arrangement: Zigzag Pins W, Pin length [P]: 5 mm, number of solder pins per potential: 1, Packaging type: Boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 5N HV/ 6-ZB-6,35 SZS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.