

INDUSTRIAL COMPONENT DATA

MKDSF 3/ 3 GY PA2,3 1098092 PHOENIX CONTACT Terminal for printed circuit board, nominal current: 24 A, pitch..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSF 3/ 3 GY PA2,3



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSF 3/ 3 GY PA2,3
Catalog number	1098092
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-6C3EA87D11
Generated	2026-08-04

Product Overview

Terminal for printed circuit board, nominal current: 24 A, pitch: 5 mm, number of poles: 3, type of connection: Connection by screw with capsule-traction, assembly: Soldering by wave direction for connection conductor/pcb: 90 °, color: grey

Terminal block for printed circuit board, nominal current: 24 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 2.5 mm², Number of rows: 1, Number of poles per row: 3, article family: MKDSF 3, pitch: 5 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 90°, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.1 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSF 3/ 3 GY PA2,3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.