

INDUSTRIAL COMPONENT DATA

MKDSN 1,5/ 3-5,08 MCBD:+-S 1161119 PHOENIX CONTACT

Printed circuit board terminal, rated current: 17.5 A, ra..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 1,5/ 3-5,08 MCBD:+-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 1,5/ 3-5,08 MCBD:+-S
Catalog number	1161119
Category	Printed circuit board terminal
Minimum order	180 Pcs
Document ID	EO-5EF2519033
Generated	2026-08-05

Product Overview

Printed circuit board terminal, rated current: 17.5 A, rated voltage (III/2): 400 V, rated cross-section: 1.5 mm², number of potentials: 3, number of rows: 1, number of poles per row: 3, article family: MKDSN 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed. Meets the requirements of the APL Port Profile Specificat

Printed circuit board terminal, rated current: 13.5 A, sizing voltage (III/2): 400 V, nominal section: 1.5 mm², Number of rows: 1, Number of poles per row: 3, item family: MKDSN 1.5, pitch: 5.08 mm, connection type:Screw connection with traction capsule, mounting: Wave welding, connection direction conductor/printed circuit board: 0°, color: green, Pin layout: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed packaging. Meets the requirements of the APL Port Profile Specification (draft 0.3)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1161119 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

13.5 mm

Number of electrical connections (EF008252)

3

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5.08 mm

Rated current I_n (EF008250)

17.5 A

Rated voltage (EF000228)

400 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Screw connection

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section multi-wired (EF007343)

0.14 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.3 mm

Length pin (EF006825)

3.5 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB fastening (EF008226)

Connecting contact

Type of fastening (EF002442)

Solder

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 1,5/ 3-5,08 MCB D:+-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.