

INDUSTRIAL COMPONENT DATA

MKDSN 1,5/ 5 PA1,3,5 1729584 PHOENIX CONTACT Terminal for printed circuit board, rated current: 13,5 A, pitc..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 1,5/ 5 PA1,3,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 1,5/ 5 PA1,3,5
Catalog number	1729584
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-421DC69F5D
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, rated current: 13,5 A, pitch: 5 mm, number of poles: 5, type of connection: Connection by screw with capsule-traction, assembly: Soldering by wave direction for connection conductor/pcb: 0 °, color: green

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of potentials: 3, number of rows: 1, number of poles per row: 5, article family: MKDSN 1.5, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Junction block C. I., pitch: 5 mm, number of poles: 5, color: green

Trade data

Order Code One million seven hundred twenty nine thousand five hundred eighty four

Packaging unit 50 pcs

Minimum order quantity 1000 pcs

Note Manufacturing to the order (no recovery)

GTIN Four trillion seventeen billion nine hundred eighteen million twenty six thousand one hundred three

Weight per piece (excluding packing) Of 0.003 KGM

Number of the customs tariff Eighty five million three hundred sixty nine thousand ten

Country of origin (Germany)

Properties of the article

Number of poles Five

Form of training the head of the screw Longitudinal slit (L)

Thread screws M3

Plot pinout Pin linear

Product Dimensions

Length [l] 8.1 mm

Width [w] 25 mm

Height [h] 13.5 mm

Not 5 mm

Installation height (without pin) 10 mm

Length of pin [P] 3.5 mm

Distance spikes 5 mm

Rated 20 mm

Dimensions for the design of printed circuit boards

Drilling diameter 1.3 mm

Distance spikes 5 mm

Indications of conditioning

Type of packaging Packed in a carton

Packaging unit Fifty

Designation packing units Quantity

Standards and specifications

Connection according to standard EN-VDE

CSA

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Period of intended use (EFUP) : 50 years

The manufacturer's declaration in the tab "Downloads" contains detailed information on hazardous substances.

Classifications

eCl@ss

eCl@ss 4.0 Twenty seven million one hundred forty one thousand one hundred nine

eCl@ss 4.1 Twenty s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 1,5/ 5 PA1,3,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.