

INDUSTRIAL COMPONENT DATA

MKDSN 1,5/ 5 RD H1L 1713440 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 1,5/ 5 RD H1L



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 1,5/ 5 RD H1L
Catalog number	1713440
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-F066C99CC4
Generated	2026-08-06

Product Overview

PCB terminal block

Terminal block for printed circuit board, rated current: 13.5 A, rated voltage (III/2): 400 V, rated cross-section: 1.5 mm², number of rows: 1, number of poles per row: 5, item family: MKDSN 1.5, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: H1L Philipps-Recess with longitudinal groove, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Red, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 3.5mm, Number of Solder Pins per Potential: 1, Packaging Type: Boxed Packaged

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1713440

Packing unit 1

GTIN 4055626313870

Custom tariff number 85369010

Item properties

Number of positions 5

Drive form screw head Philipps recess with slotted Torx (H1L)

Screw thread M3

Pin layout Linear pinning

Dimensions for the product

Length [l] 9.5 mm

Width [w] 25 mm

Height [h] 18.5 mm

Pitch 5 mm

Height (without solder pin) 15 mm

Solder pin [P] 3.5 mm

Pin spacing 5 mm

Dimension a 20 mm

Dimensions for PCB design

Hole diameter 1.3 mm

Pin spacing 5 mm

Packaging information

Type of packaging packed in cardboard

Pieces per package 50

Denomination packing units Pcs.

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss 7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 5.0EC002643ETIM 6.0EC002643

ETIM for 1713440 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

13.47 mm

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm

Rated current In (EF008250)

17.5 A

Rated voltage (EF000228)

400 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Screw connection

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable conductor cross section fine...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 1,5/ 5 RD H1L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.