

INDUSTRIAL COMPONENT DATA

MKDSN 1,5/ 7 TS BD:-11 SO 1038640 PHOENIX CONTACT

Terminal for printed circuit board, pitch: 5 mm, number of..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 1,5/ 7 TS BD:-11 SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 1,5/ 7 TS BD:-11 SO
Catalog number	1038640
Category	Printed circuit board terminal
Minimum order	80 Pcs
Document ID	EO-CF406A705D
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, pitch: 5 mm, number of poles: 7, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: green

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of rows: 1, number of poles per row: 7, article family: MKDSN 1.5, pitch: 5 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

ETIM for 1038640 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

13.47 mm

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm

Rated current I_n (EF008250)

17.5 A

Rated voltage (EF000228)

400 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Screw connection

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section multi-wired (EF007343)

0.14 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.3 mm

Length pin (EF006825)

3.5 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB fastening (EF008226)

Connecting contact

Type of fastening (EF002442)

Solder

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 1,5/ 7 TS BD:-11 SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.