

INDUSTRIAL COMPONENT DATA

**MKDSN 2,5/ 2-5,08GYSZSBD:79,80 1808268 PHOENIX
CONTACT PCB terminal block, nominal current: 24 A, nom.
volta..**

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 2,5/ 2-5,08GYSZSBD:79,80



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 2,5/ 2-5,08GYSZSBD:79,80
Catalog number	1808268
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-BC512D96FF
Generated	2026-08-03

Product Overview

PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 2, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal cross-section: 2.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: MKDSN 2.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

PCB terminal block, nominal current: 24 A, rated voltage (III/2): 400 V, nominal cross section: 2.5 mm², pitch: 5.08 mm, number of positions: 2, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1808268

Packing unit 1

GTIN 4046356707862

Custom tariff number 85369010

Drawings

Electrical parameters

Material data - contact

Dimensions for the product

Packaging information

Ambient conditions

Pull-out test

Air clearances and creepage distances

Vibration test

Environmental Product Compliance

Item properties

Connection capacity

Material data - housing

Dimensions for PCB design

General product information

Termination and connection method

Electrical tests

Temperature-rise test

Standards and Regulations

Classifications

Drawings

Diagram

Type: MKDSN 2,5/...

[Back to top](#)Item properties

Brief article description PCB terminal block

Range of articles MKDSN 2,5

Pitch 5.08 mm

Number of positions 2

Connection method Screw connection with tension sleeve

Drive form screw head Slotted (L)

Screw thread M3

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 1

Number of connections 2

Number of potentials 2

[Back to top](#)Electrical parameters

Nominal current 24 A

Nom. voltage 400 V

Rated voltage 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

[Back to top](#)Connection capacity

Connection method Screw connection with tension sleeve

pluggable Yes

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG / kcmil 24 ... 14

Conductor cross section flexible, with ferrule witho...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 2,5/ 2-5,08GYSZSBD:79,80 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.