

INDUSTRIAL COMPONENT DATA

MKDSN 2,5/ 2 BK 1932805 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 2,5/ 2 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 2,5/ 2 BK
Catalog number	1932805
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-A7B2C335FA
Generated	2026-08-04

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal cross-section: 2.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: MKDSN 2.5, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping method: H1L Philipps-Recess with longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

PCB terminal, nominal current: 24 A, reference voltage (III/2): 400 V, nominal cross-section: 2.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article range: MKDSN 2.5, pitch: 5 mm, connection type: Screw connection with ring, screw driving surface: H1L Philipps-Recess with longitudinal slot, Mounting: Wave soldering, Conductor/PCB plugging direction: 0°, Colour: Black, Pin layout: Linear pinout, Spindle length [P]: 3.5 mm, Number of pins per potential: 1, Packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1932805

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918863869

Weight per Piece (excluding packing) 2.870 g

Custom tariff number 85369010

Country of origin DE (Germany)

Item properties

Brief article description PCB terminal block

Range of articles MKDSN 2,5

Pitch 5 mm

Number of positions 2

Connection method Screw connection with tension sleeve

Drive form screw head Philipps recess with slotted Torx (H1L)

Screw thread M3

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 1

Electrical parameters

Rated current 24 A

Rated insulation voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Connection capacity

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG / kcmil 24 ... 14

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.2 mm² ... 0.75 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 0.75 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 1.5 mm²

Stripping length 6.5 mm

Torque 0.5 Nm ... 0.6 Nm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 2,5/ 2 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.