

## INDUSTRIAL COMPONENT DATA

# MKDSN 2,5/20 1708642 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 2,5/20



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | MKDSN 2,5/20                   |
| Catalog number  | 1708642                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-33B536A192                  |
| Generated       | 2026-08-05                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, dimensioning voltage (III/2): 400 V, nominal section: 2.5 mm<sup>2</sup>, Number of potentials: 20, Number of rows: 1, Number of poles per row: 20, family of articles: MKDSN 2.5, pitch: 5mm, type of connection: Screw connection with traction capsule, mounting: Wave soldering, Conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed packaging. The item can be aligned with different numbers of poles!

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

## Additional Product Information

Key Commercial Data

Orderkey 1708642

Packing unit 1

GTIN 4055626011462

Custom tariff number 85369010

Item properties

Brief article description PCB terminal block

Range of articles MKDSN 2,5

Pitch 5 mm

Number of positions 20

Connection method Screw connection with tension sleeve  
Drive form screw head Philipps recess with slotted Torx (H1L)  
Screw thread M3  
Mounting type Wave soldering  
Pin layout Linear pinning  
Number of levels 1  
Number of connections 20  
Number of potentials 20  
Electrical parameters  
Rated current 24 A  
Rated insulation voltage (III/2) 400 V  
Rated surge voltage (III/2) 4 kV  
Connection capacity  
Conductor cross section solid 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Conductor cross section AWG / kcmil 24 ... 14  
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
2 conductors with same cross section, solid 0.2 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>  
2 conductors with same cross section, flexible 0.2 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>  
2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>  
2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Stripping length 6.5 mm  
Torque 0.5 Nm ... 0.6 Nm  
Material data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics Tin-p...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 2,5/20 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.