

INDUSTRIAL COMPONENT DATA

MKDSO 2,5/ 3-R GN PA1,3 1757114 PHOENIX CONTACT

Printed circuit board terminal, rated current: 24 A, rated v..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSO 2,5/ 3-R GN PA1,3



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSO 2,5/ 3-R GN PA1,3
Catalog number	1757114
Category	Printed circuit board terminal
Minimum order	200 Pcs
Document ID	EO-D1B4427E22
Generated	2026-08-05

Product Overview

Printed circuit board terminal, rated current: 24 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 3, item family: MKDSO 2.5/.. -R, pitch: 5 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: green, Pin length [P]: 3.5 mm, number of soldering pins per potential: 1. Partially equipped variant with right side pin output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSO 2,5/ 3-R GN PA1,3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.