

INDUSTRIAL COMPONENT DATA

MKKDS 1,5/13-5,08 BD:SO 1 1706837 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDS 1,5/13-5,08 BD:SO 1



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDS 1,5/13-5,08 BD:SO 1
Catalog number	1706837
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-C12BF9A514
Generated	2026-08-06

Product Overview

PCB terminal block

Terminal block for printed circuit board, rated current: 17.5 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 1.5 mm², Number of rows: 2, Number of poles per row: 13, article family: MKKDS 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

PCB terminal block, nominal current: 17.5 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 13, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0°, color: green

Your advantages

Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceAllows connection of two conductorsConductor connection on several levels enables higher contact densityThe latching on the side enables various numbers of positions to be combinedKey Commercial Data

Orderkey 1706837

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918315320

Weight per Piece (excluding packing) 43.200 g
Custom tariff number 85369010
Country of origin DE (Germany)
Material data - housing
Housing color green (6021)
Dimensions for the product
Length [l] 21.4 mm
Width [w] 68.58 mm
Height (without solder pin) 25.2 mm
Solder pin [P] 3.5 mm
Dimension a 60.96 mm
Dimensions for PCB design
Hole diameter 1.3 mm
Packaging information
Type of packaging packed in cardboard
Pieces per package 50
Denomination packing units Pcs.
Air clearances and creepage distances
Voltage 250 V
Standards and Regulations
Connection in acc. with standard EN-VDE
CSA
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
eCI@ss
eCI@ss 4.0 27141109....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDS 1,5/13-5,08 BD:SO 1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.