

INDUSTRIAL COMPONENT DATA

MKKDS 3/16-5,08 BU BD:33-64 1728840 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDS 3/16-5,08 BU BD:33-64



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDS 3/16-5,08 BU BD:33-64
Catalog number	1728840
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-A865CC681A
Generated	2026-08-02

Product Overview

PCB terminal block

Terminal block for printed circuit board, Number of poles per row: 16, item family: MKKDS 3, pitch: 5.08 mm, color: blue, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1728840

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356146760

Weight per Piece (excluding packing) 74.240 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [L] 22.3 mm

Pitch 5.08 mm

Dimension a 76.2 mm

Width [w] 83.82 mm

Height 31.5 mm

Height [h] 36.5 mm

Solder pin [P] 5 mm

Hole diameter 1.3 mm

General

Range of articles MKKDS 3

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 22 A

Nominal cross section 2.5 mm²

Solder pin surface

Internal cylindrical gage A3

Stripping length 7 mm

Number of positions 16

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDS 3/16-5,08 BU BD:33-64 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.