

INDUSTRIAL COMPONENT DATA

MKKDS 3/19 GY 1077263 PHOENIX CONTACT PCB terminal block, pitch: 5 mm, number of positions: 19, color: gray,...

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDS 3/19 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDS 3/19 GY
Catalog number	1077263
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-D9F6E9E47B
Generated	2026-08-06

Product Overview

PCB terminal block, pitch: 5 mm, number of positions: 19, color: gray, Pin layout: Linear pinning, Solder pin [P]: 5 mm
Terminal block for printed circuit board, nominal current: 22 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm²,
number of rows: 2, number of poles per row: 19, article family: MKKDS 3, pitch: 5 mm, connection type: Screw connection
with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave Soldering, Conductor/PCB Connection
Direction: 0°, Color: Grey, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 5mm, Number of Soldering Pins per
Potential: 1, Packaging Type: Boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1077263

Packing unit 1

GTIN 4055626789958

Custom tariff number 85369010

Item properties

Dimensions for PCB design

Standards and Regulations

Classifications

Dimensions for the product

Packaging information

Environmental Product Compliance

Item properties

Number of positions 19

Drive form screw head Slotted (L)

Screw thread M3

Pin layout Linear pinning

[Back to top](#)Dimensions for the product

Length [l] 22.3 mm

Width [w] 99.06 mm

Height [h] 36.5 mm

Pitch 5 mm

Height (without solder pin) 31.5 mm

Solder pin [P] 5 mm

Dimension a 91.44 mm

[Back to top](#)Dimensions for PCB design

Hole diameter 1.3 mm

[Back to top](#)Packaging information

Type of packaging packed in cardboard

Pieces per package 10

Denomination packing units Pcs.

[Back to top](#)Standards and Regulations

Connection in acc. with standard EN-VDE

[Back to top](#)Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.1 27261100

eCl@ss 6.0 27261100

eCl@ss 7.0 27440401

eCl@ss 8.0 27440401

eCl@ss 9.0 27440401

[Back to top](#)ETIM

ETIM 5.0 EC002643

ETIM 6.0 EC002643

ETIM 7.0 EC002643

[Back to top](#)

ETIM for 1077263 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

36.5 mm

Number of levels (EF002659)

2

Modular spacing connections (EF006827)

5 mm

Rated current I_n (EF008250)

22 A

Rated voltage (EF000228)

400 V....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDS 3/19 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.