

INDUSTRIAL COMPONENT DATA

MKKDS 5/ 2-6,35 Z1L 1812522 PHOENIX CONTACT Printed circuit board terminal, rated current: 41 A, rated volta..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDS 5/ 2-6,35 Z1L



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDS 5/ 2-6,35 Z1L
Catalog number	1812522
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-42F50854B8
Generated	2026-08-04

Product Overview

Printed circuit board terminal, rated current: 41 A, rated voltage (III/2): 630 V, rated cross-section: 4 mm², number of rows: 2, number of poles per row: 2, item family: MKKDS 5, pitch: 6.35 mm, connection type: Screw connection with traction capsule, screw clamping form: Z1L Pozidriv with longitudinal groove, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Green, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 5.2mm, Number of Solder Pins per Potential: 1, Packaging Type: Boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDS 5/ 2-6,35 Z1L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.