

INDUSTRIAL COMPONENT DATA

MKKDSG 3/ 2 BD:12-11 1537249 PHOENIX CONTACT PCB terminal, rated current: 17.5 A, rated voltage (III/2): 400..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDSG 3/ 2 BD:12-11



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDSG 3/ 2 BD:12-11
Catalog number	1537249
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-73B3358E09
Generated	2026-08-05

Product Overview

PCB terminal, rated current: 17.5 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of rows: 2, number of poles per row: 2, item family: MKKDSG 3, pitch: 5 mm, connection type: Screw connection with pull capsule, screw clamping form: L Longitudinal groove, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Green, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 5mm, Number of Solder Pins by Potential: 1, Packing Type: Boxed Packaging

Terminal block for printed circuit board, number of poles per row: 2, Item family: MKKDSG 3, pitch: 5 mm, connection type: Screw connection with pull capsule, screw clamping form: L Longitudinal groove, mounting: Wave soldering, connection direction conductor/printed circuit board: 0°, color: green, Pin arrangement: Linear Pin Arrangement, Pin Length [P]: 5mm, Packaging Type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataItem PropertiesProduct Line COMBICON Terminals M

Product Type Printed Circuit Board Terminal

Product Family MKKDSG 3

Number of poles 2

Step 5 mm

Number of rows 2

Pin Design Linear Pin Arrangement

Number of Solder Pins Per Potential 1

Electrical PropertiesNominal Current IN 17.5 A

Nominal voltage UN 400 V

Degree of pollution 3

Sizing voltage (III/3) 250 V

Dimensioning transient voltage (III/3) 4 kV

Dimensioning voltage (III/2) 400 V

Dimensioning Transient Voltage (III/2) 4 kV

Nominal voltage (II/2) 630 V

Dimensioning transient voltage (II/2) 4 kV

Connection dataConnection technology

Construction Card terminal, alignable

Nominal Section 2.5 mm²

Connecting Conductors

Connection type Screw connection with traction capsule

Rigid conductor section 0.2 mm² ... 4 mm²

Flexible conductor section 0.2 mm² ... 2.5 mm²

AWG Conductor Section 24 ... 12

Flexible conductor section with toe cap, without plastic sleeve 0.25 mm² ... 1.5 mm²

Flexible conductor section with toe cap, with plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with the same cross-section, rigid 0.2 mm² ... 1.5 mm²

2 conductors with the same cross-section, flexible 0.2 mm² ... 1.5 mm²

2 conductors of equal cross-section, flexible with toe cap, without plastic sleeve 0.25 mm² ... 0.75 mm²

2 conductors with the same cross-section, flexible with TWIN toe cap with plastic sleeve 0.5 mm² ... 0.5 mm²

Peel Length 7 mm

Tightening torque 0.5 Nm ... 0.6 Nm

assemblyType of mounting Wave soldering

Pin Design Linear Pin A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDSG 3/ 2 BD:12-11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.