

INDUSTRIAL COMPONENT DATA

MKKDSG 3/ 2 BD:32-31 1537252 PHOENIX CONTACT PCB terminal, rated current: 17.5 A, rated voltage (III/2): 400..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDSG 3/ 2 BD:32-31



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDSG 3/ 2 BD:32-31
Catalog number	1537252
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-8B281D310B
Generated	2026-08-03

Product Overview

PCB terminal, rated current: 17.5 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of rows: 2, number of poles per row: 2, item family: MKKDSG 3, pitch: 5 mm, connection type: Screw connection with pull capsule, screw clamping form: L Longitudinal groove, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Green, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 5mm, Number of Solder Pins by Potential: 1, Packing Type: Boxed Packaging

PCB terminal block, rated current: 17.5 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 2.5 mm², number of rows: 2, number of poles per row: 2, product series: MKKDSG 3, pitch: 5 mm, connection type: Screw connection with cage, screw attachment form: L Longitudinal slot, mounting: Wave soldering, Conductor/board connection direction: 0°, Color: Green, Pin Layout: Linear Pinning, Pin Length [P]: 5mm, Number of Solder Pins per Potential: 1, Package Type: Packed in Carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataArticle featuresProduct Line COMBICON Terminals M

Product Type PCB terminal block

Product Family MKKDSG 3

No. of poles 2

Step 5 mm

Number of rows 2

Pin Layout Linear Pinning

Number of Welding Pins per Potential 1

Electrical characteristics Rated Current I_N 17.5 A

Rated voltage U_N 400 V

Degree of pollution 3

Sizing voltage (III/3) 250 V

Sizing impulse voltage (III/3) 4 kV

Sizing voltage (III/2) 400 V

Sizing Impulse Voltage (III/2) 4 kV

Sizing voltage (II/2) 630 V

Sizing Impulse Voltage (II/2) 4 kV

Connection data Connection technology

type Modular PCB terminal block

Nominal cross-section 2.5 mm²

Conductor connection

Link Screw connection with cage

Rigid conductor cross-section 0.2 mm² ... 4 mm²

Flexible conductor cross-section 0.2 mm² ... 2.5 mm²

Conductor cross-section AWG 24 ... 12

Flexible conductor cross-section with cable lug without plastic collar 0.25 mm² ... 1.5 mm²

Flexible conductor cross-section with mounted lug and plastic collar 0.25 mm² ... 2.5 mm²

2 conductors of identical cross-section, rigid 0.2 mm² ... 1.5 mm²

2 conductors of identical flexible cross-section 0.2 mm² ... 1.5 mm²

2 conductors of the same flexible cross-section with ferrule without plastic collar 0.25 mm² ... 0.75 mm²

2 conductors of identical cross-section flexible with TWIN ferrule with plastic collar 0.5 mm² ... 0.5 mm²

Length of the section to be stripped 7 mm

Tightening torque 0.5 Nm ... 0.6 Nm

Montage Mounting type Wave Soldering

Pin Layout Linear Pinning

Appliance type screw h...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDSG 3/ 2 BD:32-31 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.