

INDUSTRIAL COMPONENT DATA

MKKDSN 1,5/ 4-5,08 TS 1708436 PHOENIX CONTACT PCB terminal block, pitch: 5.08 mm, number of positions: 4, co..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDSN 1,5/ 4-5,08 TS



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDSN 1,5/ 4-5,08 TS
Catalog number	1708436
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-E1E70CFCAD
Generated	2026-08-05

Product Overview

PCB terminal block, pitch: 5.08 mm, number of positions: 4, color: green

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 400 V, nominal section: 1.5 mm², number of rows: 2, number of poles per row: 4, article family: MKKDSN 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave soldering, conductor/PCB connection direction: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, number of soldering pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1708436

Packing unit 1

GTIN 4055626000121

Custom tariff number 85369010

Dimensions

Length [l] 18.3 mm

Pitch 5.08 mm

Dimension a 15.24 mm

Width [w] 22.86 mm

Height 19.1 mm

Height [h] 22.6 mm

Solder pin [P] 3.5 mm

Pin spacing 10 mm

Hole diameter 1.3 mm

General

Range of articles MKKDSN 1,5

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 13.5 A

Nominal cross section 1.5 mm²

Solder pin surface

Internal cylindrical gage A1

Stripping length 6 mm

Number of positions 4

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.14 mm²

2 conductors with same cross section, solid max. 0.75 mm²

2 conductors with same cross section, stranded min. 0.14 mm²

2 conductors with same cross section, stranded max. 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 0.5 mm²

Standards and Regulations...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDSN 1,5/ 4-5,08 TS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.