

INDUSTRIAL COMPONENT DATA

MKKDSNH 1,5/ 3-5,08 BKBDWH:-14 1016687 PHOENIX CONTACT Terminal for printed circuit board, rated voltage: 40..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDSNH 1,5/ 3-5,08 BKBDWH:-14



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDSNH 1,5/ 3-5,08 BKBDWH:-14
Catalog number	1016687
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-B46F1F1882
Generated	2026-08-06

Product Overview

Terminal for printed circuit board, rated voltage: 400 V, pitch: 5,08 mm, number of poles: 3, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: black

Terminal block for printed circuit board, nominal current: 13.5 A, dimensioning voltage (III/2): 400 V, nominal section: 1.5 mm², Number of potentials: 3, Number of rows: 1, Number of poles per row: 3, article family: MKKDSNH 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, Connection direction conductor/printed circuit board: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDSNH 1,5/ 3-5,08 BKBDWH:-14 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.