

INDUSTRIAL COMPONENT DATA

MM-TML (EX4,2)R C1 TR/BK 0803979 PHOENIX CONTACT Label

Brand: PHOENIX CONTACT | Manufacturer Part Number: MM-TML (EX4,2)R C1 TR/BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MM-TML (EX4,2)R C1 TR/BK
Catalog number	0803979
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-E99B38A9DC
Generated	2026-08-05

Product Overview

Label

Label, Roll, transparent/black, unlabeled, labelable with: THERMOFOX, THERMOMARK GO, THERMOMARK GO. K, mounting class: glued, usable surface: endless x 3.2 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0803979

Packing unit 1 pc

Catalog page Page 53 (C-3-2017)

GTIN 4055626212548

Weight per Piece (excluding packing) 50.600 g

Custom tariff number 96121010

Country of origin CN (China)

Dimensions

Length (b) 8 m

Width (a) 4.2 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color transparent

Type adhesive

Components free from silicone, halogen, and cadmium

Material Polyester

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0 24190208 eCl@ss 4.1 24190208 eCl@ss 5.0 27149103 eCl@ss 5.1 27141100 eCl@ss 6.0 27149100 eCl@ss 7.0 27149129 eCl@ss 8.0 27149129 eCl@ss....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MM-TML (EX4,2)R C1 TR/BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.