

INDUSTRIAL COMPONENT DATA

MM-WMS-2 6,4 (EX10)R C1 YE/BK 1116187 PHOENIX CONTACT Heat-shrink sleeve, Roll, yellow/black, unlabeled, lab..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MM-WMS-2 6,4 (EX10)R C1 YE/BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MM-WMS-2 6,4 (EX10)R C1 YE/BK
Catalog number	1116187
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-4F914FA15D
Generated	2026-08-06

Product Overview

Heat-shrink sleeve, Roll, yellow/black, unlabeled, labelable with: THERMOMARK GO, THERMOFOX, THERMOMARK GO. K, Cable Diameter Range: 3.2 ... 6.4 mm: without printing, mounting type: sliding, Number of individual indexes: 1, text field height: 8.5 mm, text field width: 1800 mm

Heat shrink tubing, Roll, yellow/black, unlabeled, labelable with: THERMOMARK GO, THERMOFOX, mounting class: slippage, cable diameter range: 3.2 ... 6.4 mm, usable surface: endless x 8.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > MS Material**

Additional Product Information

ETIM for 1116187 Cable terminations and insulation products (EC001530)

Feature Name

Feature Value

Model (EF000010)

Roller shape

Type (EF001139)

Medium-walled

Tooththing (EF009649)

None

Material (EF002169)
Other
Core diameter (EF005497)
3.2 mm
Cable diameter (EF002356)
3.2 mm
Length (EF001438)
11.5 mm
Colour (EF000007)
Yellow-black
Fluorescent (EF009518)
No
With label space (EF003456)
Yes
Imprint (EF000131)
Other
Mounting method (EF000003)
Suspend

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MM-WMS-2 6,4 (EX10)R C1 YE/BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.