

INDUSTRIAL COMPONENT DATA

IB IL TEMP 4/8 RTD/EF-PAC 2897402 PHOENIX CONTACT

Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL TEMP 4/8 RTD/EF-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL TEMP 4/8 RTD/EF-PAC
Catalog number	2897402
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-F6B7DEE320
Generated	2026-07-31

Product Overview

Inline terminal

Inline, Temperature recording module, Analogue RTD inputs: 8 (for resistive temperature sensors), connection technology: 4 conductors, transmission rate on local bus: 500 kBit/s, protection rating: IP20, including inline connectors and marking fields

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2897402

Packing unit 1 pc

Catalog page Page 165 (C-6-2017)

GTIN 4046356288026

Weight per Piece (excluding packing) 221.600 g

Custom tariff number 85389091

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 48.8 mm

Height 119.8 mm

Depth 71.5 mm

Note on dimensions Housing dimensions

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 221.6 g

Note on weight specifications with connectors

Operating mode Process data mode with 5 words/1 word PCP

Diagnostics messages Failure of the internal I/O supply I/O error message sent to the bus coupler

Failure of or insufficient communications power ULI/O error message sent to the bus coupler

User error Error message in the process data

Interfaces

Designation Inline local bus

No. of channels 2

Connection method Inline data jumper

Transmission speed 500 kbps

Transmission physics Copper

Inline potentials

Designation Communications power (UL)

Supply voltage 7.5 V DC (via voltage jumper)

Current consumption typ. 95 mA

max. 120 mA

Designation....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL TEMP 4/8 RTD/EF-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.