

INDUSTRIAL COMPONENT DATA

EMD-BL-V-230-PT 2903524 PHOENIX CONTACT Monitoring relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMD-BL-V-230-PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMD-BL-V-230-PT
Catalog number	2903524
Category	Voltage monitoring relay
Minimum order	1 Pcs
Document ID	EO-92F84B6FFE
Generated	2026-08-06

Product Overview

Monitoring relay

Control relay for monitoring single-phase voltages 24 V AC/DC or 230 V AC, undervoltage or Window, 1 switched contact, with push-in connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data

Orderkey 2903524

Packing unit 1 pc

Catalog page Page 262 (C-5-2017)

GTIN 4046356747288

Weight per Piece (excluding packing) 72.000 g

Custom tariff number 85364900

Country of origin AT (Austria)

Dimensions

Width 17.5 mm

Height 88 mm

Depth 65.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 70 °C

Connection data

Connection method Push-in connection

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 2.5 mm²

Stripping length 8 mm

General

Status display Yellow LED

Overvoltage category III, 300 V basic insulation (DIN EN 60947-5-1)

Rated insulation voltage 300 V (Supply circuit/measuring circuit (DIN EN 60947-5-1))

Electromagnetic compatibility Conformance with EMC Directive 2004/108/EC

Noise emission EN 61000-6-3

Noise immunity EN 61000-6-2

Color gray

Mounting position any

Assembly instructions on standard DIN rail NS 35 in accordance with EN 60715

Conformance CE-compliant

UL, USA/Canada UL/C-UL listed UL 508

Standards and Regulations

Electromagnetic compatibility Conformance with EMC Directive 2004/108/EC

Noise emission EN 61000-6-3

Noise immunity EN 61000-6-2

Low Voltage Directive Conformance with LV directive 2006/95/EC

Conformance CE-compliant

UL, USA/Canada UL/C-UL listed UL 508

Environmental...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMD-BL-V-230-PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.