INDUSTRIAL COMPONENT DATA

PT 2,5-PE/3L 3210542 PHOENIX CONTACT Motor terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-PE/3L

Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-PE/3L
Catalog number	3210542
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-05EB6143A7
Generated	2026-08-03

Product Overview

Motor terminal
Motor terminal block, four levels, connection type: push-in connection, cross-section: 0.14 mm² - 4 mm², AWG: 26 - 12, width: 5.2 mm, height: 91.1 mm, colour: grey, mounting type: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3210542
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 71 (C-1-2017)
GTIN 4046356867108
Weight per Piece (excluding packing) 26.520 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 4
Number of connections 7
Nominal cross section 2.5 mm²
Color gray

Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 60947-7-1/IEC 60947-7-2
Nominal current IN 20 A (with a 2.5 mm² conductor cross section)
Maximum load current 25 A (with 4 mm² conductor cross section)
Nominal voltage UN 800 V
Connection in acc. with standard IEC 60947-7-1/IEC 60947-7-2
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2 kV
Checking the mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.14 mm² / 0.2 kg
2.5 mm² / 0.7 kg
4 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-PE/3L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.