

**INDUSTRIAL COMPONENT DATA**

# UM-ALU 4-100,5 FRONT 200 2200948 PHOENIX CONTACT

## Components of electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-ALU 4-100,5 FRONT 200



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | UM-ALU 4-100,5 FRONT 200         |
| Catalog number  | 2200948                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-3857F00AEA                    |
| Generated       | 2026-08-03                       |

### Product Overview

Components of electronic housing

Extruded profile boxes, Front plate with basic profile, color: aluminum color, width: 101.8 mm, length: 201.3 mm, depth: 2 mm, recommended for UM-ALU 4 side elements-.. COVER PA..

Profile, Front base profile, width: 101.8 mm, length: 201.3 mm, depth: 2 mm, recommended for side elements UM-ALU 4..COVER PA..

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 2200948

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 744 (C-1-2013)

GTIN 4046356720939

Weight per Piece (excluding packing) 115.400 g

Custom tariff number 76061191

Country of origin DE (Germany)

General

Housing type Press-drawn section housings

Housing material Aluminum

Color (RAL) aluminum color

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

Dimensions

Length 201.3 mm

Height 2 mm

Width 101.8 mm

Depth 100.5 mm

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 10.0.127182701eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss

6.027182000eCl@ss 7.027182701eCl@ss 8.027182701eCl@ss 9.027182701

ETIM 3.0EC001031ETIM 4.0EC000721ETIM 5.0EC002779ETIM 6.0EC002779

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.231261501

ETIM for 2200948 Low-voltage industrial controls and switchgear (EC002779)

Feature Name

Feature Value

Type of enclosure (EF003086)

Open

Housing connectable (EF003088)

No

Suitable for rail mounting (EF003972)

No

Wall mounting possible (EF003973)

No

With integrated PCB-mounting connection system (EF003087)

No

Material (EF002169)

Aluminium

Surface finishing (EF006569)

Other

Colour (EF000007)

Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-ALU 4-100,5 FRONT 200 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.