

INDUSTRIAL COMPONENT DATA

MPT 0,5/10-2,54 BD:1-9,0 1888629 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MPT 0,5/10-2,54 BD:1-9,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	MPT 0,5/10-2,54 BD:1-9,0
Catalog number	1888629
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-2A37927421
Generated	2026-08-03

Product Overview

PCB terminal block

Terminal block for printed circuit board, rated current: 6 A, rated voltage (III/2): 160 V, rated cross-section: 0.5 mm², number of rows: 1, number of poles per row: 10, item family: MPT 0.5, pitch: 2.54 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave soldering, conductor/PCB connection direction: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, number of soldering pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1888629

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918343125

Weight per Piece (excluding packing) 2.920 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [L] 6.2 mm

Pitch 2.54 mm

Dimension a 22.86 mm

Width [w] 25.86 mm

Height 8.5 mm

Height [h] 12 mm

Solder pin [P] 3.5 mm

Hole diameter 1.1 mm

General

Range of articles MPT 0,5

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 63 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 6 A

Nominal cross section 0.5 mm²

Maximum load current 6 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 4.5 mm

Number of positions 10

Screw thread M1,6

Tightening torque, min 0.12 Nm

Tightening torque max 0.15 Nm

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 0.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 0.34 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.34 mm²

Conductor cross section AWG min. 26

Conductor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MPT 0,5/10-2,54 BD:1-9,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.