


## INDUSTRIAL COMPONENT DATA

# MSLK 4 1410013 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSLK 4



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | MSLK 4                |
| Catalog number  | 1410013               |
| Category        | Ground terminal block |
| Minimum order   | 10 Pcs                |
| Document ID     | EO-AE6A20319A         |
| Generated       | 2026-08-04            |

## Product Overview

Ground modular terminal block

Ground terminal, number of connections: 1, connection type: Screw connection, cross-section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting class: NS 15, color: silver

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 1410013

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4017918021078

Weight per Piece (excluding packing) 6.330 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 1

Nominal cross section 2.5 mm<sup>2</sup>

Color silver

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 5 kV

Maximum power dissipation for nominal condition 0.77 W

Maximum load current 34 A (with 4 mm<sup>2</sup> conductor cross section)

Open side panel Yes

Dimensions

Length 27.5 mm

Width 5 mm

Height 18 mm

Connection data

Connection method Screw connection

Conductor cross section solid min. 0.2 mm<sup>2</sup>

Conductor cross section solid max. 4 mm<sup>2</sup>

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 2.5 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.2 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm<sup>2</sup>

Screw thread M3

Tightening torque, min 0.6 Nm

Tightening torque max 0.8 Nm

Standards and Regulations

Connection in acc. with standard UL

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC 4-Nonylphenol, ethoxylated

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141118eCl@ss 4.127141118eCl@ss 5.027141118eCl@ss 5.127141100eCl@ss...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSLK 4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.