

INDUSTRIAL COMPONENT DATA

MSTB 2,5/15-STZ13-5,08 AU TS 1008082 PHOENIX CONTACT

Connector for printed circuit board, number of poles: 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5/15-STZ13-5,08 AU TS



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTB 2,5/15-STZ13-5,08 AU TS
Catalog number	1008082
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-03932BD02A
Generated	2026-08-06

Product Overview

Connector for printed circuit board, number of poles: 15, pitch: 5,08 mm, type of connection: Connection by screw with capsule-wheel drive, color: green, surface, contacts: Gold

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Gold, contact type: Female connection, Number of potentials: 15, Number of rows: 1, Number of poles per row: 15, number of connections: 15, family of articles: MSTB 2.5/.. -ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, conductor connection direction/printed circuit board: 0 °, Strain relief: STZ13 Traction discharge 39.9 X 46 mm, Stecksyst.: CLASSIC COMBICON, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Connector for printed circuit board, nominal current: 12 A, voltage and sizing (III/2): 320 V, number of poles: 15, pitch: 5,08 mm, type of connection: Connection by screw with capsule-wheel drive, color: green, surface contacts: Tin

Data commercial

Key order One million eight thousand eighty two

Packing unit 50 pcs

Key selling AAAFAA -

Minimum order quantity 50 pcs

EAN Four trillion fifty five billion six hundred twenty six million four hundred eighty thousand seven hundred ninety four

Unit weight (excluding packaging) 29,472 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Dimensions

Length [l] 63,9 mm

Width [w] 76.2 mm

Height [h] 15,5 mm

Step 5,08 mm

Average 71,12 mm

Overview

Family of articles MSTB 2,5/..-ST

Number of poles Fifteen

Type of connection Connection by screw with capsule-traction

Nominal cross section 2.5 mm²

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Space of time for the intended use (FEUP): 50 years

You will find information about hazardous substances in the manufacturer's declaration in the "Downloads" tab

Ratings

eCl@ss

eCl@ss 5.1 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 6.0 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 7.0 Twenty seven million four hundred forty thousand three hundred nine

eCl@ss 8.0 Twenty seven million four hundred forty thousand three hundred nine

eCl@ss 9.0 Twenty seven million four hundred forty thousand...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5/15-STZ13-5,08 AU TS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.