

**INDUSTRIAL COMPONENT DATA**

# MSTB 2,5/17-ST 1754740 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5/17-ST



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | PHOENIX CONTACT |
| MPN / Reference | MSTB 2,5/17-ST  |
| Catalog number  | 1754740         |
| Category        | Cable connector |
| Minimum order   | 50 Pcs          |
| Document ID     | EO-5196F76626   |
| Generated       | 2026-08-03      |

## Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 17, number of rows: 1, number of poles: 17, number of connections: 17, family of articles: MSTB 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

## Additional Product Information

Key Commercial Data

Orderkey 1754740

Packing unit 50 pc

Catalog page Page 126 (CC-2005)

GTIN 4017918028916

Weight per Piece (excluding packing) 27.860 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [ l ] 18.2 mm

Width [ w ] 85 mm  
Height [ h ] 15 mm  
Pitch 5 mm  
Dimension a 80 mm  
General  
Range of articles MSTB 2,5/..-ST  
Number of positions 17  
Connection method Screw connection with tension sleeve  
Insulating material group I  
Rated surge voltage (III/3) 4 kV  
Rated surge voltage (III/2) 4 kV  
Rated surge voltage (II/2) 4 kV  
Rated voltage (III/3) 250 V  
Rated voltage (III/2) 320 V  
Rated voltage (II/2) 630 V  
Connection in acc. with standard EN-VDE  
Nominal current IN 12 A  
Nominal cross section 2.5 mm<sup>2</sup>  
Maximum load current 12 A (with a 2.5 mm<sup>2</sup> conductor cross section)  
Insulating material PA  
Flammability rating according to UL 94 V0  
Internal cylindrical gage A3  
Stripping length 7 mm  
Screw thread M3  
Tightening torque, min 0.5 Nm  
Tightening torque max 0.6 Nm  
Connection data  
Conductor cross section solid min. 0.2 mm<sup>2</sup>  
Conductor cross section solid max. 2.5 mm<sup>2</sup>  
Conductor cross section flexible min. 0.2 mm<sup>2</sup>  
Conductor cross section flexible max. 2.5 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5/17-ST with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.