

INDUSTRIAL COMPONENT DATA

MSTB 2,5/20-ST-5,08 AU 1749771 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5/20-ST-5,08 AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTB 2,5/20-ST-5,08 AU
Catalog number	1749771
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-5F680E49CB
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Gold, contact type: Female connection, Number of potentials: 20, Number of rows: 1, Number of poles per row: 20, number of connections: 20, family of articles: MSTB 2.5/.. -ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, driver/printed circuit board connection direction: 0 °, Stecksystem: CLASSIC COMBICON, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1749771

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918214432

Weight per Piece (excluding packing) 30.940 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 18.3 mm

Width [w] 101.6 mm

Height [h] 15 mm

Pitch 5.08 mm

Dimension a 96.52 mm

General

Range of articles MSTB 2,5/..-ST

Number of positions 20

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A (with a 2.5 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5/20-ST-5,08 AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.