

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/4,0-140/M12MS SMI 1563148 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/4,0-140/M12MS SMI



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/4,0-140/M12MS SMI
Catalog number	1563148
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-E861E6E69F
Generated	2026-08-06

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 4-Pole, PUR/PVC, Yellow, M12 Straight Male Connector, Coding: A Coded, A Straight Male M12, Coding: A Coded, Cable Length: 4 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1563148

Packing unit 5 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356302548

Weight per Piece (excluding packing) 172.450 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 4 m

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 250 V AC

250 V DC

Number of positions 4

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR/PVC yellow

Cable type (abbreviation) 140

Cable abbreviation LiYY-11Y

UL AWM style 20549

Conductor cross section 0.34 mm²

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.5 mm ± 0.05 mm

Thickness, insulation approx. 0.3 mm (Core insulation)

≥ 0.38 mm (Outer cable sheath)

approx. 0.35 mm (Inner sheath)

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

External sheath, color yellow

External cable diameter D 5.2 mm ± 0.2 mm

Smallest bending radius, fixed installation 52 mm

Smallest bending radius, movable installation 52 mm

Number of bendi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/4,0-140/M12MS SMI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.