

INDUSTRIAL COMPONENT DATA

TFKC 2,5/ 2-ST-5,08 BK LCRD/BU 1705849 PHOENIX CONTACT Plug-in part, rated current: 12 A, number of poles: 2..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TFKC 2,5/ 2-ST-5,08 BK LCRD/BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	TFKC 2,5/ 2-ST-5,08 BK LCRD/BU
Catalog number	1705849
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-6E76250522
Generated	2026-08-06

Product Overview

Plug-in part, rated current: 12 A, number of poles: 2, pitch: 5.08 mm, connection type: Push-in spring connection, color: black, contact surface: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 4, family of articles: TFKC 2.5/.. -ST, pitch: 5.08 mm, connection type: Push-in spring connection, conductor connection/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Plug component, nominal current: 12 A, number of positions: 2, pitch: 5.08 mm, connection method: Push-in spring connection, color: black, contact surface: Tin

Your advantages

Time saving push-in connection, tools not requiredPotentials can be easily looped through - ideal for BUS applicationsIntuitive use through colour coded actuation leverCan be combined with the MSTB 2´,5 rangeQuick and convenient testing using integrated test optionKey Commercial Data

Orderkey 1705849

Packing unit 1

GTIN 4046356803724

Custom tariff number 85366990

General

Range of articles TFKC 2,5/...-ST

Type of contact Female connector

Number of positions 2

Connection method Push-in spring connection

Rated voltage (III/3) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TFKC 2,5/ 2-ST-5,08 BK LCRD/BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.