


INDUSTRIAL COMPONENT DATA

PT 1,5/ 4-PVH-3,5-A BKBDWH-I4B 1711742 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 4-PVH-3,5-A BKBDWH-I4B



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/ 4-PVH-3,5-A BKBDWH-I4B
Catalog number	1711742
Category	Cable connector
Minimum order	250 Pcs
Document ID	EO-8E103ACFAA
Generated	2026-08-05

Product Overview

PCB terminal block

Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 6 A, nominal voltage (III/2): 200 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: PT 1.5/..-PVH-A, pitch: 3.5 mm, connection type: Screw connection with wire protection bracket, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, plug-in system: COMBICON PST 1.0, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1711742

Packing unit 1

GTIN 4055626255149

Custom tariff number 85366990

Dimensions

Length [l] 11 mm

Width [w] 14 mm

Height [h] 11 mm

Pitch 3.5 mm

Dimension a 3.5 mm

General

Range of articles PT 1,5/..-PVH-A

Number of positions 4

Connection method Screw connection with wire protector

Insulating material group I

Rated voltage (III/2) 200 V

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Flammability rating according to UL 94 V0

Screw thread M2

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 5.0EC002638ETIM 6.0EC002638

ETIM for 1711742 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of poles (EF001391)

4

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Angle contact/conductor connection (EF007546)

Other

Rated current In (EF008250)

6 A

Rated voltage (EF000228)

200 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable cond...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 4-PVH-3,5-A BKBDWH-I4B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.