

INDUSTRIAL COMPONENT DATA

MSTB 2,5/ 5-ST-5,08 OG BDNZX22 1715572 PHOENIX CONTACT PCB connector, nominal current: 12 A, rated voltage (..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5/ 5-ST-5,08 OG BDNZX22



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTB 2,5/ 5-ST-5,08 OG BDNZX22
Catalog number	1715572
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-C8A8FC3CE7
Generated	2026-08-05

Product Overview

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 5, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, color: orange, contact surface: Tin
Connector for printed circuit board, nominal section: 2.5 mm², color: orange, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of rows: 1, number of poles: 5, family of articles: MSTB 2.5/..-ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1715572

Packing unit 1

GTIN 4055626968858

Custom tariff number 85366990

Drawings

Electrical parameters

Material data - contact
Dimensions for the product
Ambient conditions
Pull-out test
Air clearances and creepage distances
Durability tests (B)
Environmental and durability tests (E)
Item properties
Connection capacity
Material data - housing
Packaging information
Termination and connection method
Mechanical tests according to standard
Mechanical tests (A)
Climatic tests (D)
Classifications
Drawings
Diagram
Type: MSTB 2,5/...-ST-5,08 with CC 2,5/...-G-5,08 P26THR
Diagram
Type: MSTB 2,5/...-ST-5,08 with CCV 2,5/...-G-5,08 P26THR
Diagram
Type: MSTB 2,5/...-ST-5,08 with CCVA 2,5/...-G-5,08 P26THR
Diagram
Type: MSTB 2,5/...-ST-5,08 with MDSTB 2,5/...-G-5,08
Diagram
Type: MSTB 2,5/...-ST-5,08 with MDSTBA 2,5/...-G-5,08
Diagram
Type: MSTB 2,5/...-ST-5,08 with MDSTBW 2,5/...-G-5,08
Diagram
Type: MSTB 2,5/...-ST-5,08 with MDSTBV 2,5/...-G-5,08
Diagram
Type: MSTB 2,5/...-ST-5,08 with MVSTBU 2,5/...-GB-5,08
Diagram
Type: MSTB 2,5/...-ST-5,08 with MSTB 2,5/...-G-5,08
Diagram
Type: MSTBP 2,5/...-ST-5,08 with MDSTBVA 2,5/...-G-5,08
Diagram
Type: MSTB 2,5/...-ST(-5,08) with EMSTBVA 2,5/...-G(-5,08)
Diagram
Type: MSTB 2,5/...-ST-5,08 with MSTBW 2,5/...-G-5,08
Diagram
Type: MSTB 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: MSTB 2,5/...-ST-5,08 with MSTBV 2,5/...-G-5,08
Diagram
Type: MSTB 2,5/...-ST-5,08 with MDSTB 2,5/...-G1-5,08

Diagram

Type: MSTB 2,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5/ 5-ST-5,08 OG BDNZX22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.