

INDUSTRIAL COMPONENT DATA

MC 1,5/ 5-G-3,5 AU CP3 1701330 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 5-G-3,5 AU CP3



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 5-G-3,5 AU CP3
Catalog number	1701330
Category	Printed circuit board connector
Minimum order	250 Pcs
Document ID	EO-40EB7080EA
Generated	2026-08-04

Product Overview

Feed-through header

Printed circuit board base case, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: MC 1.5/.. -G, pitch: 3.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1701330

Packing unit 1

GTIN 4046356526258

Custom tariff number 85366930

Item properties

Brief article description Feed-through header

Plug-in system MINI COMBICON

Type of contact Male connector

Range of articles MC 1,5/..-G

Pitch 3.5 mm
Number of positions 5
Mounting type Wave soldering
Pin layout Linear pinning
Locking without
Number of levels 1
Number of connections 5
Number of potentials 5
Electrical parameters
Rated current 8 A
Rated insulation voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Material data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Selective coating
Metal surface contact area (top layer) Gold (0.8 - 1.4 μm Au)
Metal surface contact area (middle layer) Nickel (2 - 3 μm Ni)
Metal surface soldering area (top layer) Gold (0.8 - 1.4 μm Au)
Metal surface soldering area (middle layer) Nickel (2 - 3 μm Ni)
Material data - housing
Insulating material PBT
Insulating material group IIIa
CTI according to IEC 60112 225
Flammability rating according to UL 94 V0
Dimensions for the product
Length [l] 9.2 mm
Width [w] 18.9 mm
Height [h] 10.65 mm
Pitch 3.5 mm
Height (without solder pin) 7.25 mm
Solder pin [P] 3.4 mm
Pin dimensions 0.8 x 0.8 mm
Dimension a 14 mm
Packaging information
Type of packaging packed in cardboard
Pieces per package 50
Denomination packing units Pcs.
Ambient conditions
Ambient temperature (storage/transportation)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 5-G-3,5 AU CP3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.